

MIRO<sup>®</sup> Industries Inc. engineers a support system to your specifications with non-penetrating duct supports

## The MIRO<sup>®</sup> Advantage:



- 20 year warranty standard for all supports.
- Non-penetrating eliminates unnecessary roof penetrations.
- Labor savings no cutting, welding, or fabrication
- Even distribution of weight all systems are designed not to exceed 3.0 PSI
- Base size range stocked sizes include 6-DS, 8-DS, and 10-DS (Specifications on back).
- Support types open, enclosed, or stacked (customizable).
- **Pre-assembled** support structure will arrive pre assembled to jobsite.
- Clean, professional project uniformity provides quality to your business or project



Offering a range of exceptional products, all from top quality manufacturers.

MKT Manufacturers' Representatives | 460 Grim Lane, Suite 2, York, PA 17406 | MAIN 717-764-9090 | FAX 717-764-8182 www.mktduct.com/products



## **Specification Information**

## 6-DS

Frame constructed of strut and MIRO's patented bases allows for sturdy support without roof membrane penetration or damage.

Duct rests on a 1 5/8" x 13/16" strut, adjustable in height Base size: 9" x 15.25" Weight: Not to exceed 3.0 PSI Base Material: Polycarbonate, Stainless Steel, and Hot Dip Galvanized







Frame constructed of strut and MIRO's patented bases allows for sturdy support without roof membrane penetration or damage.

Also available in: Enclosed or Stacked Duct rests on 1 5/8" x 1 5/8" strut, adjustable in height Base sizes: 16" x 18" Weight: Not to exceed 3.0 PSI Base Material: Polycarbonate, Stainless Steel, and Hot Dip Galvanized

## **10-DS**

The 10-DS or "H" type support is designed specifically for square and round duct work.

Base sizes: 19" x 23" Weight: Not to exceed 3.0 PSI Base Material: Polycarbonate, Stainless Steel, and Hot Dip Galvanized



MIRO Industries, Inc. ("MIRO") conducts all sales transactions in accordance with its Standard Sales Terms and Conditions available at http://www.miroind.com/termsconditions/ In the event that any of the terms or conditions hereon modify or conflict with any provisions, terms, or conditions in MIRO's Standard Terms and Conditions, the terms of MIRO's Standard Sales Terms and Conditions shall control.